

DSPT-19

BATTERY POWERED SEALLESS PLASTIC STRAPPING TOOL FOR 0.75 INCH POLYESTER STRAP

The DuBose Strapping Model DSPT-19 Battery Powered Strapping Tool is a lightweight but powerful tool designed to apply 0.75 inch PET Polyester strapping in a variety of industrial applications such as brick, wood, fiber and steel industries. The requirement for the use of steel strapping in numerous applications can be eliminated using the DSPT-19 in combination with DuBose high quality Polyester strapping.



FEATURES

- DESIGNED FOR MAXIMUM COMFORT, EFFICIENCY, SAFETY, AND EASE OF USE
- COMPACT AND LIGHTWEIGHT
- 0.75 INCH / 0.050 PET STRAP CAPACITY
- HIGH APPLIED STRAP TENSION
- TWO MAKITA 14.4 V / 3.0AH LITHIUM-ION BATTERY PACKS AND CHARGER INCLUDED
- LONG BATTERY LIFE AND RAPID CHARGE TIME
- DEWALT MOTORS WITH REPLACEABLE BRUSHES
- ONE BUTTON RAPID TENSIONING
- TENSION LEVEL AND WELD TIME FULLY PROGRAMABLE FOR CONSISTENT PACKAGING RESULTS

SPECIFICATIONS

Package type	Flat and round surfaces (min. diam.—28inch)
Strap quality	PET
Strap width	0.75 inch
Strap thickness	0.031 inch to - 0.050 inch
Maximum. Tension	Approximately 900 Lbs./Force dependent on the strap quality
Minimum Tension	215 lbs./Force
Max. Tensioning speed	Approximately 40 ft./min
Joint	Friction weld seal with approximately 75% average joint strength dependent on strap quality
Battery	Makita Lithium-Ion 14.4 VDC / 3.0 Ah
Charger	Makita 120 VAC
Strap Cycles per charge	Approximately 200 dependent upon strap Type, welding and tension settings
Battery Charge Time	20 minutes
Weight	Approximately 9 Lbs. including battery
Width	5.125 inches
Length	13.75 inches
Height	6.5 inches
DSPT-19	Order Item Number: 13501

OPTIONAL ITEMS

- STEEL PROTECTION PLATE FOR USE ON BRICK AND ROUGH SURFACES
- RUBBER HOUSING PROTECTOR



For more information or to request pricing, please contact your local DuBose Strapping distributor or call our sales department at 800-354-3020.

