

DuBose Strapping Titan HKE-HD

Manual Seal-less Combination Tool
For Regular Duty and High Tensile Steel
Strapping



- Torque limit ensures consistent tension
- Easy Strap application.
- Tensioning, Sealing and Cutting in two easy steps
- “No seal joint” Technology.
- Easy wear part replacement.

Titan HKE-HD Manual Combination E-Series Tool

Lightweight, heavy duty tool for easy and efficient strapping.

Use the Titan HKE-HD steel strapping tool to apply steel strapping, without the use of metal seals. The functions of tensioning, sealing and cutting of strapping are accomplished with one, easy to use tool, resulting in a seal joint that is stronger than joints made with standard metal seals.

The new HKE-HD tool is the result of constant development of the Titan "No-Seal-Joint" technology for strap ping tools. Weighing 10 lbs., it is the lightest available Heavy Duty strapping tool, which means easier and safer operation for vertical and horizontal strapping. A built in torque limiter ensures consistent strap tensioning.

The HKE-HD is a durable tool that will provide years of reliable service. Sealing occurs by means of a rocking punch mechanism, so just 1/3 of the seal is made at a time. This means less physical power is required for actuation, and less wear of the mechanical parts.



The sealing mechanism of the E-Series Tool

The genuine Titan "No-Seal-Joint"



Prevents injuries: The uniquely shaped strap end leaves no sharp edges.

Technical data	Strapping tool HKE-HD
Seal:	Titan "No-Seal-Joint"
Steel strap grades:	Regular Duty and High Tensile strap
Strap width:	3/4 inch
Strap thickness range:	.023 to .031 inch
Strap tensioning:	Manual

