

## DuBose Strapping

### Titan PKE

### Pneumatic Seal-less Combination Tool For Regular Duty and High Tensile Steel Strapping



- **Pneumatic Tension Motor ensures consistent strap tension**
- **Effortless Sealing action**
- **Tensioning, Sealing and Cutting in two easy steps**
- **“No seal joint” Technology**
- **Easy wear part replacement**
- **Tension adjustable to 1750 pounds**

## Titan PKE Pneumatic Seal-less Combination Tool

**Automatic tool for easy and efficient strapping.**

Use the Titan PKE pneumatic steel strapping tool to apply steel strapping without the use of metal seals. The functions of tensioning, sealing and cutting of strapping are accomplished with one, easy to use tool, resulting in a seal joint that is stronger than joints made with standard metal seals. The PKE pneumatic strapping tool ensures consistent strap tension and effortless joint sealing.

The new PKE tool is the result of constant development of the Titan “No-Seal-Joint” technology for strap ping tools. The pneumatic tensioning and sealing system means easier and safer operation for vertical and horizontal strapping.

The PKE is a durable tool that will provide years of reliable service. Sealing occurs by means of a rocking punch mechanism, so just 1/3 of the seal is made at a time. This means less physical power is required for actuation, and less wear of the mechanical parts.



The sealing mechanism of the E-Series Tool

The genuine Titan “No-Seal-Joint”



Prevents injuries: The uniquely shaped strap end leaves no sharp edges.

<b>Technical Data</b>	<b>Model Titan PKE</b>
<b>Seal Type</b>	Titan “ No Seal Joint”
<b>Strap Qualities</b>	Regular Duty and High Tensile Strap
<b>Strap Width</b>	1/2, 5/8, and 3/4 inch
<b>Strap Thickness</b>	.015 to .031 inch
<b>Applied Tension</b>	1100 to 1750 pounds force
<b>Air Supply</b>	60 to 95 psi
<b>Air Consumption</b>	25 CFM

