

DuBose Strapping

Titan Max L

Pneumatic Pusher Combination Tool for
Round Bundling Applications
Regular Duty and High Tensile Steel
Strapping



- **Pneumatic Tension Motor ensures consistent strap tension**
- **Effortless Sealing action**
- **Tensioning, Sealing and Cutting in two easy steps**
- **Adjustable to 1500 pounds tension**
- **Easy wear part replacement.**
- **Light Weight**

Titan Maxi L Pneumatic Pusher Combination Tool

Automatic tool for easy and efficient strapping.

Use the Titan Max L pneumatic steel strapping tool to apply steel strapping on round bundle applications. The functions of tensioning, sealing and cutting of the strap are accomplished with one, easy to use tool. The Max L pneumatic combination strapping tool ensures consistent strap tension and effortless joint sealing.

The pneumatic tensioning and sealing system means easier and safer operation for vertical and horizontal strapping operations. Tensioning occurs when the tool pushes against the seal until the tension motor stalls, the push of the sealing button activates the sealing jaws to crimp the seal and cut the strapping simultaneously.

The Max L is a durable tool that will provide years of reliable service. No external pneumatic tubing and piston diaphragm to damage means less service time. Easy to change wear parts means less maintenance time. Top or side mounted air connections are available for different application requirements.



Technical Data	Model Titan Max L
Seal Type	Long Pusher Seal
Joint	Double Notch
Strap Qualities	Regular Duty and High Tensile Strap
Strap Width	¾ inch
Strap Thickness	.023 to .031 inch
Applied Tension	Adjustable to 1500 pounds force
Air Supply	80 to 95 psi
Air Consumption	25 CFM

